


MR354 SERIES Duplexer, 4 cavity mobile, 5 to 10 MHz separation, 380-512 MHz

- Four highly stable temperature compensated helical resonators
- Enclosure made of lightweight and rugged aluminum extrusion
- 50 Watts power handling with 50 dB Tx to Rx isolation
- Minimum Tx-Rx spacing of 5 MHz, maximum of 10 MHz

Sinclair's MR354 series of mobile duplexers are compact units, fabricated from lightweight, rugged aluminum extrusion, which affords maximum structural integrity. Carefully temperature-compensated resonators are designed to minimize variations due to changing operating environments. These duplexers provide superior performance for trunking and conventional applications, and may also be used as low-power base station duplexers.

When ordering, please refer to the chart below for the model number, and also specify the Tx and Rx frequencies. Different connector configurations are subject to various list price. Customization is also available. Please contact your Sinclair Sales Representative or Customer Service Representative for more information.



BNC connector model shown.

Part Number	Connector	Frequency range
MR354B-1	BNC(f)	406-440 MHz
MR354B-2	BNC(f)	440-480 MHz
MR354B-3	BNC(f)	480-512 MHz
MR354B-4	BNC(f)	380-400 MHz
MR354N-1	N(f)	406-440 MHz
MR354N-2	N(f)	440-480 MHz
MR354N-3	N(f)	480-512 MHz
MR354N-4	N(f)	380-400 MHz
MR354T-1	TNC(f)	406-440 MHz
MR354T-2	TNC(f)	440-480 MHz
MR354T-3	TNC(f)	480-512 MHz
MR354T-4	TNC(f)	380-400 MHz

Note:

The MR series of compact mobile duplexers can be re-tuned within the sub-band for which the unit was designed, as long as the Tx/Rx separation remains the same. Tuning procedures are available upon request. Significant Tx/Rx frequency separation re-tuning requires shipping the units back to the factory. Please call for details.

Region	United States	Europe, Middle East and Africa	Caribbean and Latin America	Canada and rest of the world
Telephone	USA: 1 800 263 3275	International: +44 (0) 1487 84 28 19	International: +1 905 726 7676	Canada: 1 800 263 3275 International: +1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salesla@sinctech.com	salescan@sinctech.com
Product Specification Sheet		MR354 SERIES	Issue: 0	Dated: 20-09-19

Electrical Specifications

Frequency Range	MHz	380 to 512	
Number of Cavities - Low Pass Side		2	
Number of Cavities - High Pass Side		2	
Connectors		Various	*1
Input VSWR (max)		1.5:1	
Insertion loss (max)	dB	1	
Impedance	Ω	50	
Isolation - Tx noise suppression at Rx (min)	dB	50	
Isolation - Rx carrier suppression at Tx (min)	dB	50	
Average Input Power (max)	W	50	
Frequency Separation Range	MHz	5 to 10	

Mechanical Specifications

Width	in (mm)	4.1 (104)
Depth	in (mm)	9 (229)
Length/ Height	in (mm)	1.3 (33)
Finish		chemical conversion
Weight	lbs (kg)	1.8 (0.82)
Actual shipping weight	lbs (kg)	2 (0.91)
Shipping dimensions	in (mm)	13x9x3 (330x229x76)

Environmental Specifications


Temperature range	°F (°C)	-22 to +140 (-30 to +60)
-------------------	---------	--------------------------

Notes

*1 : See previous page for details

Ordering Information

Specify Tx and Rx frequencies when ordering.



Span 10 MHz
Response curve (typical), 5MHz Sep.

www.sinclaire.com

Region	United States	Europe, Middle East and Africa	Caribbean and Latin America	Canada and rest of the world
Telephone	USA: 1 800 263 3275	International: +44 (0) 1487 84 28 19	International: +1 905 726 7676	Canada: 1 800 263 3275 International: +1 905 727 0165
E-mail	salesusa@sinclaire.com	salesuk@sinclaire.com	salesla@sinclaire.com	salescan@sinclaire.com
Product Specification Sheet		MR354 SERIES	Issue: 0	Dated: 20-09-19